Noise Barriers European Standards – CE Marking





Giovanni Brero

ENBF President www.enbf.org



« pauca sed matura » C. F. Gauss

Let's call things with their name

Noise Reducing Device?? better:

Larmschutz Barriere antirumore Pantalla antiruido Noise barriers

Ecran antibruit Geluidsscherm Ekrany Akustyczne

Giovanni Brero – ENBF in Sarajevo – 21th may 2015

ENBF Effective Members

- Asociación Nacional de Industriales de Pantallas y dispositivos Anti-ruido (ANIPAR), Spain + Portugal
- Association Professionnelle des Réalisateurs d'Ecrans Acoustiques (APREA), France
- Deutscher Verband f
 ür L
 ärmschutz an Verkehrswegen e.V. (DVLV), Germany
- Unione Nazionale delle Industrie delle Costruzioni Metalliche (UNICMI), Italy


Associated Members

- Bayer Sheet Europe, Belgium
- CIR Ambiente, Italy
- DECEUNINCK NV, Belgium
- EVONIK, Austria
- KOHLHAUER GmbH, Germany
- MICE SA, Belgium
- Van Campen Industries B.V, Netherlands
- Alfa Bond Kohlhauer Sp. z o. o. , Poland
- LS Lublow GmbH, Germany
- Akripol, Slovenia





A PATH FOR EU LEGISLATION AND TECH STANDARDS




ENBF TASK N.1 - To provide informative support and cooperation to the bodies in charge of writing European legislation and European technical standards.



ENBF TASK N.2 - To set up the basis for cooperation between industry, public administration and other relevant stakeholders

NEED OF CLEAR COMMUNICATION TO THE PUBLIC



70 + 70 = 73 dB(A) ??

ENBF TASK N.3 - to develop communication tools in order to spread knowledge and expertise to a large audience.

NOISE BARRIERS ACROSS EU NEED OF MERGING EXPERIENCES

ENBF TASK N.4

To exchange knowledge and expertise on products and solutions among members of the federation

Giovanni Brero – ENBF in Sarajevo – 21th may 2015

A HER A REP RE-

THE VARIETY OF THE MARKET MAY LEAD TO BARRIERS TO TRADE ?



Noise barriers are construction products under CPR (Construction Product Regulation n. 305/2011) that means:

hEN 14388:2005 is the only reference harmonised European standard written by CEN under a specific EU Commission Mandate

Manufacturers are asked to :

- Declare NOISE BARRIER performance of essential characteristics
- Affix the CE marking >> to take responsibility for the conformity of the NOISE BARRIER with the declared performances


DoP (Declaration of Performance)

Noise barrier (NOT a part if it) is the product to be incorporated into a road infrastructure and its performance has to be declared for the essential characteristics:

	CPR
1- M	echanical resistance and stability
2- Sa	afety in case of fire
(ygiene, health and the environment ughout the life cycle + safety of kers
4- Sa	afety and accessibility in use
5- Pr	otection against noise
Ene	ergy economy and heat retention rgy efficiency of construction work ng construction and dismantling
7-Su	stainable use of natural resources

CE marking for Noise Barriers to be installed alongside Road Infrastructures ENBF – Guidelines & Recommendations (http://www.enbf.org/outcomes.htm)

DoP of the noise barrier system What is CE marking?




NOISE BARRIER SYSTEM is the ROAD EQUIPMENT requiring for CE marking


PERFOMANCE is to be assessed on the noise barrier system

It is NOT a mere collection of single components technical datasheets

Often may happen that:



It should be like that:



Giovanni Brero – ENBF in Sarajevo – 21th may 2015

<u>hEN does not fix product requirements</u> unless threshold values are established within the standards by Mandate


<u>Authorities or Member State are in charge of establishing</u> <u>requirements</u> but shall not impede the use of construction products bearing the CE marking, when the declared performances correspond to the requirements for such use in that Member State

Members State shall <u>not introduce other regulations</u> (Directive 98/34/EC - notification of new regulations)


Public Procurement must be open to competition (EU Directives on public procurement)

Use of hEN 14388 has to be made by all actors (regulators, engineers producers, contractors) in a "common European technical language"

CE marking >> DoP of the noise barrier system Acoustic performance: insulation + absorption




Reverberant chamber method (EN 1793.1 and 2)



In situ method (CEN TS 1793.5 - EN 1793.6) Evaluation to be perfomed on the noise barrier system


ACOUSTIC PERFOMANCE

Present State of the Art on Methods for CE marking



ACOUSTIC PERFOMANCE

Methods for Qualifying Noise Barrier Effectiveness



CE marking >> DoP of the noise barrier system Structural performance (EN 1794-1)





Manufacturers shall declare maximum loads noise barrier are able to withstand provided maximum deflection of post and panels are not exceeded. Loads to be considered are wind load and variable loads due to passing vehicles

Structural calculation is currently performed on the supporting posts.

Laboratory tests are recommended for the noise panels


Noise barrier system - Structural performance RAIL APPLICATION






Alternating pressure and suction forces due to passing train main cause fatigue effect

CE marking >> DoP of the noise barrier system Structural performance: errant vehicles impact



Crash test to be perfomed according to EN 1317 in case of integrated noise and safety barrier

DoP of the noise barrier system Structural performance: risk from falling debris



Risk from falling debris may occur in case of noise barrier installed on bridges or critical positions – (EN 1794-2)

Use of intrinsic resistant materials is essential as th evaluation of performance is to be made on the whole barrier (use of safety cables, secure posts etc)

DoP of the noise barrier system Safety in use : behaviour in case of fire


Noise barrier performance are currently evaluated by testing the system against brush fire EN 1794-3 Annex A.

Classification of products according to Euroclasses (EN 13501) is recommended for some intended use as per attach table:

Class	Intended use	Test performances
1	Tunnels and total covers	Class B or better according to EN 13501
2	Partial covers, on bridges and near houses	Class E or better according to EN 13501
3	All other situations where fire could be relevant	Test results according to Annex A

Table B.1 — Classification of reaction to fire for noise reducing devices (informative)

DoP of the noise barrier system Long term durability EN 14389.1,2



Material specification (corrosion protective layers, wood treatment) are essential for long term durability. Also to be considered assembling system, water drainage..

Toward a protocol for Sustainability Assessment



Thanks for your attention

for futher info pls see

www.enbf.org

Giovanni Brero – ENBF in Sarajevo – 21th may 2015